

MODEL 200 H.O. - V6

SPECIFICATIONS



Model	a. E200DHL b. E200HSL c. E200HVL d. E200DHX e. E200HCX
Shaft Length mm (in) / Color	a. 508 (20") Blue b. / c. 508 (20") White d. / e. 635 (25") White
Weight kg (lbs)	a. / b. 228 (503) c. 235 (518) d. / e. 238 (524)
Engine Type	Loop Charged V6 90° E-TEC Direct Injection
Bore x Stroke mm (in)	98 x 73 (3.854 x 2.858)
Displacement cc (cu in)	3279 (200)
Ignition System	IDI Fast Rise Inductive Ignition
Starter	Electric
Trim Method	FasTrak™ Power Trim and Tilt
Propshaft kilowatts (HP)*	Factory Tuned for High Performance
Full Throttle Operating Range	4500-5800 RPM
Gear Ratio	a. / b. 1.86:1 High Speed c. / d. / e. 1.85:1
Fuel Induction	E-TEC Direct Fuel Injection with stratified low RPM combustion mode
Alternator	Variable Voltage Computer Controlled 133 Amp** / 1800 watt output with Regulator
Cooling	Pressure and Temperature Controlled Water Cooled
Steering	Remote
Limited Warranty	3 Years Non-Declining
Emissions Compliance	EPA CARB 3 STAR European Union



* Power Ratings: Evinrude® outboards are power rated in accordance with NMMA procedure using the International Council of Marine Industry Associates (ICOMA) standard 28/83.

** 133 Amp current calculated at 13.5 V. Net dedicated battery charging power output is 50 Amp.