

MODEL 40 SPECIFICATIONS



Model	a. E40DPL b. E40DSL c. E40DTL d. E40DRL
Shaft Length mm (in) / Color	a. / c. / d. 508 (20") Blue b. 508 (20") White
Weight kg (lbs)	a. / b. 109 (240) c. 113 (251) d. 105 (232)
Engine Type	Inline 2-cylinder E-TEC Direct Injection
Bore x Stroke mm (in)	91 x 66 (3.600 x 2.588)
Displacement cc (cu in)	863 (52.7)
Ignition System	IDI Fast Rise Inductive Ignition
Starter	a. / b. / c. Electric d. Rope
Trim Method	a. / b. / c. Power Trim and Tilt d. Manual Tilt
Propshaft kilowatts (HP)*	30 kw (40 HP) @ 5500 RPM
Full Throttle Operating Range	5000-6000 RPM
Gear Ratio	2.67:1
Fuel Induction	E-TEC Direct Fuel Injection with stratified low RPM combustion mode
Alternator	Variable Voltage Computer Controlled 81 Amp** / 1100 watt output with Regulator
Cooling	Pressure and Temperature Controlled Water Cooled
Steering	a. / b. Remote or Accessory Tiller c. / d. Tiller Standard
Limited Warranty	3 Years Non-Declining
Emissions Compliance	EPA CARB 3 STAR European Union



* Power Ratings: Evinrude® outboards are power rated in accordance with NMMA procedure using the International Council of Marine Industry Associates (ICOMA) standard 28/83.

** 81 Amp current calculated at 13.5 V. Net dedicated battery charging power output is 25 Amp.